










TUBES & ACCESSOIRES PNEUMATIQUES

ASSÈCHEUR D'AIR

Caractéristiques	No. de pièce	Filets	Flot d'air max. (L/MIN)	Filtration (µM)	Pression max. (MPa)
	AMG150	1/8 - 1/4 - 3/8	300	5 (STD) 2 - 10 20 - 40 70-100	5 (STD) 2 - 10 20 - 40 70-100
	AMG250	1/8 - 1/4	300		
	AMG350	3/8 - 1/2	750		
	AMG450	1/2 - 3/4	1500		
	AMG550	3/4 - 1	3500		
	AMG650	1 - 1 1/2	6000		
	AMG850	1 1/2 - 2	12000		

Permet l'assèchement de l'air à 99%, à l'entrée ou à la sortie des lignes d'air • Support de montage optionnel

AUTRES PRODUITS DISPONIBLES SUR DEMANDE

<p>Silencieux</p>  <p>Série NAN</p>	<p>Valve anti-retour «check-valve»</p>  <p>Série NAK</p>	<p>Valve à solénoïde</p> 
<p>Actuateur : Contrôle de vitesse</p>  <p>Série NAS</p>	<p>Contrôle débit («flow control»)</p>  <p>Série NAS</p>	<p>Cylindre à l'air</p> 

AUTRES PRODUITS DISPONIBLES SUR DEMANDE

